

TABLE OF CONTENTS 目 录

Effects of Tapered Roller Crowning on Contact Stress Distribution

(圆锥滚子修形对接触副应力分布的影响)

Z. Z. HE, M. H. SHAO, J. H. WU..... 299

Semi-Active Fuzzy Control of the Magneto-Rheological Damping Device for CNC Milling Machine

(数控铣床磁流变减振装置及半主动模糊控制)

W. N. LIU, C. M. LI, Z. G. LIU..... 307

The Study of the Relation of 316L Stainless Steel Diffusion Welding Process Parameters

Based on the Weibull Distribution and the Reliability

(基于威布尔分布 316L 不锈钢扩散焊接工艺参数与可靠性关系研究)

Z. L. AN, L. ZHANG, Y. J. LI, M. F. HOU..... 315

Study and Application on Flexible Assembly Tooling Technology of UAV

(无人机柔性装配工装技术研究及应用)

T. J. YANG, M. ZHANG, Q. WU..... 322

The Heat Formed Technology Research of Needle Punched Filter on New Style Heat Treatment

(基于新型热处理方式的针刺过滤毡热定型技术研究)

X. M. LI..... 329

Research on the Key Technology and Technology System of Intelligent Shipyard

(智能船厂关键技术及技术体系研究)

D. LUO, Z. J. BAO, B. T. LIU, Z. L. GUAN, C. J. WANG, W. C. JIANG..... 334

Kinetic Modeling of a Novel 3-CRU Translational Parallel Mechanism

(一种新型 3-CRU 并联机构的动力学建模)

D. J. GUO, Y. M. LI, B. LI..... 344

The Optimal Structure Parameters of Hydrocyclone with Dual Cone Based on Orthogonal Design

(正交试验条件下的双锥旋分器结构参数的确定)

F. LI, Z. H. XU..... 352

Control Technology of Two-Axis Laser Processing Platform Based on AEROTECH

(基于 AEROTECH 双轴平台的血管支架加工控制技术)

H. JIANG, T. SHI, J. H. DANG..... 360

Numerical Simulation Study of Spiral-Wound Exchanger

(缠绕管换热器性能数值模拟研究)

X. B. HUANG, Z. B. ZHU, P. H. ZHUANG, J. W. ZHANG..... 367

**Design and Research of Drilling Tool for Inner Wall Blind Hole in Logging Instrument Shell
(测井仪器外壳内壁盲孔钻削装置设计与研究)**

Z. WANG.....376

**Design and Research of Stirling Engine Heat Exchange Device
(斯特林发动机热交换装置的设计与研究)**

X. L. DU, Z. L. CHEN.....382

**Research on Modeling and Compensation of Pose Error of Assembly Robot
(装配机器人位姿误差建模与补偿研究)**

J. Z. HUI, J. Y. LEI, J. L. ZHANG, G. W. ZHAO.....391

**External Characteristics and Experiment Analysis of Variable Shock Absorbers of Vehicles
(汽车可变阻尼减振器外特性及试验分析)**

S. S. LI.....400